

MAGTEK®

**The Technology
Behind The Transaction**

U S B S w i p e R e a d e r



Complete Card Reading Solutions



NEW!

- Powered USB bus—no external power supply required.
- Hardware compatible with any computer or terminal with an USB interface
- Single, dual or three track capability
- Bi-directional read capability
- Reads encoded cards that meet ISO/ANSI/CDL/AAMVA standards
- Up to 1,000,000 passes with ISO-conforming cards
- Includes USB interface cable
- USB HID class vendor-defined MSR emulation or keyboard emulation
- Available in black or white



Specifications

OPERATING

Reference Standards:
ISO, ANSI, CDL and AAMVA

Power Input:
From USB

Recording Method:
Two-frequency coherent phase (F2F)

Message Format:
Vendor defined emulation

Card Speed:
3 to 50 IPS

MTBF:
Electronics: 125,000 hours
Head: 1,000,000 passes

MECHANICAL

Dimensions:
Length: 3.94" (100mm)
Width: 1.28" (32,5mm)
Height: 1.23" (31,3mm)

Weight:
Reader with cable: 5.8 oz. (1,65g)

Connector:
USB

ENVIRONMENTAL

Temperature:
Operating: 32°F to 131°F (0°C to 55°C)
Storage: -22°F to 158°F (-30°C to 70°C)

Humidity:
Operating: 10% to 90% noncondensing
Storage: Up to 100% noncondensing

Altitude:
Operating: 0-10,000 ft. (0-3,048m)
Storage: 0-50,000 ft. (0-15,240m)

Ordering Information

Track 2, pearl white	P/N 21040105
Track 1 & 2, pearl white	P/N 21040103
Track 1, 2 & 3, pearl white	P/N 21040101
Track 2, black	P/N 21040106
Track 1 & 2, black	P/N 21040104
Track 1, 2 & 3, black	P/N 21040102

MAGTEK

20725 S. Annalee Avenue
Carson, CA 90746
Phone: (310) 631-8602
Fax: (310) 631-3956

Internet: <http://www.magtek.com>

1-888-624-8350